

# FABTEK

## FACTORY INSTALLED TANK INSULATION

432 East South Street • Plano, IL 60545

Ph: 630.552.3622 • Fax: 630.552.8220

[www.fabtekaero.com](http://www.fabtekaero.com)



**EXCEPTIONAL VALUE**  
**EXTRAORDINARY QUALITY**

Tank is wrapped with a 1" Ceramic Fiber Blanket rated to 2600° F and Clad in Aluminum Jacketing with Embossed Stucco Finish.

# TANK INSULATION FEATURES



## Aluminum Jacketing (Cladding) .020" Thickness

- The Premier Protective Outer Surface for Tank Insulation
- Protects the Tank from Physical Damage, UV Exposure, Corrosive Atmospheres and Water
- Stucco Embossed Finish
- 3 mil Thick Polyfoam Moisture Barrier Heat Laminated to Inner Surface

## Ceramic Fiber Insulation (RCF) 1" Thickness

- Used Primarily for Industrial High Temperature Insulating Applications
- Rated to 2600 Degrees F (1425 Degrees C)
- Non-Combustible, Insoluble, Non-Reactive
- Provides the Heat Resistance of a Hard Refractory with Greater Insulation Value



All neatly installed at the factory and caulked with NSF rated industrial grade silicone sealant.



432 East South Street • Plano, IL 60545  
Ph: 630.552.3622 • Fax: 630.552.8220  
[www.fabtekaero.com](http://www.fabtekaero.com)

